PRODUCT RECOMMENDATION

# MERLO TELESCOPIC HANDLERS, ROTATING ROTO 45.21 TJ

## ENGINE Deutz BF6M-1012

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Kroontrak CVT 10W-40** | **Agrisynth MSP 10W-40** | **Agridiesel MSP 15W-40** |

*Change every 400 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Kroontrak CVT 10W-40** | **Agrisynth MSP 10W-40** | **Agridiesel MSP 15W-40** |

*Change every 100 hours*

## DIFFERENTIAL

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 1000 hours*

## GEARBOX

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 1000 hours*

## HUB REDUCTIONS

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 1000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# MERLO TELESCOPIC HANDLERS, ROTATING ROTO 45.21 TJ

## TRANSMISSION HYDROSTATIC

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Perlus H 46** | | |
| *Change every 1000 hours* | | |

## HYDRAULIC SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Perlus H 46** | | |
| *Change every 1000 hours* | | |

## BOOM SLIDING SURFACES

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC BRAKE SYSTEM AND ACCELERATOR

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

## SWING REDUCTION UNIT

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367