PRODUCT RECOMMENDATION

MITSUBISHI FORKLIFT TRUCKS, DIESEL FD14

ENGINE Mitsubishi
Capacity: 6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 30		

Check every 10 hours, change every 200 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Check every 10 hours, change every 200 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
HDX 20W-20		

Check every 10 hours, change every 200 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		

Check every 10 hours, change every 200 hours

DIFFERENTIAL
Capacity: 4,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 6 months/ 1200 hours

TRANSMISSION Powershift
Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 6 months/ 1200 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MITSUBISHI FORKLIFT TRUCKS, DIESEL FD14

TRANSMISSION MECHANICAL
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 6 months/ 1200 hours

HYDRAULIC SYSTEM MECHANICAL TRANSMISSION
Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 12 months/ 2400 hours

HYDRAULIC SYSTEM POWERSHIFT TRANSMISSION
Capacity: 28 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 12 months/ 2400 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Perlus H 22		

Change every 12 months/ 2400 hours

HYDRAULIC BRAKE SYSTEM
Capacity: 0,13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 12 months/ 2400 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MITSUBISHI FORKLIFT TRUCKS, DIESEL FD14

GREASE POINTS/NIPPLES CHASSIS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

GREASE POINTS/NIPPLES MAST SLIDING SURFACES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 8,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

STEERING GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367