

MITSUBISHI FORKLIFT TRUCKS, DIESEL

FD90

**ENGINE**

Capacity: 13,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**HDX 30****PRODUCT RECOMMENDATION 2****HDX 10W***Check every 10 hours, change every 200 hours***USE**

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1**HDX 20W-20***Check every 10 hours, change every 200 hours***DIFFERENTIAL FRONT**

Capacity: 20 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Change every 6 months/ 1200 hours***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****Gearlube GL-4 80W***Change every 6 months/ 1200 hours***TRANSMISSION Powershift**

Capacity: 22 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF-A***Change every 6 months/ 1200 hours*

MITSUBISHI FORKLIFT TRUCKS, DIESEL

FD90



HYDRAULIC SYSTEM

Capacity: 143 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 12 months/ 2400 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		

Change every 12 months/ 2400 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,51 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 12 months/ 2400 hours

GREASE POINTS/NIPPLES CHASSIS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

COOLING SYSTEM

Capacity: 23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

MITSUBISHI FORKLIFT TRUCKS, DIESEL FD90

**WHEEL BEARINGS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.