

MITSUBISHI FORKLIFT TRUCKS, LPG/PETROL FGC25



ENGINE Mitsubishi

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 30*Change every 200 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

HDX 10W*Change every 200 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

HDX 20W-20*Change every 200 hours*

DIFFERENTIAL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 6 months/ 1200 hours*

TORQUE-DRIVE TRANSMISSION

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 6 months/ 1200 hours*

MITSUBISHI FORKLIFT TRUCKS, LPG/PETROL FGC25



HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Perlus H 46	Perlus H 32

Change every 12 months/ 2400 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		

Change every 12 months/ 2400 hours

GREASE POINTS/NIPPLES CHASSIS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

GREASE POINTS/NIPPLES MAST SLIDING SURFACES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

MITSUBISHI FORKLIFT TRUCKS, LPG/PETROL FGC25



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.