

NEW HOLLAND WHEELED EXCAVATORS

MH/WE MH PLUS CNH 667TA/BEC TIER 3A

(2008-2012)



ENGINE CNH 667TA/BEC
Capacity: 13,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 500 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 250 hours

DIFFERENTIAL RIGID AXLE
Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL STEERED AXLE
Capacity: 11 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS RIGID AXLE
Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS STEERED AXLE
Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

RIGID AXLE
Capacity: 7,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM
Capacity: 170 liter (Tank), Capacity: 250 liter (Total)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Perlus H 68

Change every 36 months/ 3000 hours

NEW HOLLAND WHEELED EXCAVATORS

MH/WE MH PLUS CNH 667TA/BEC TIER 3A

(2008-2012)



SLEWING RING GEARING

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

COOLING SYSTEM

Capacity: 25 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 2000 hours

SWING REDUCTION UNIT

Capacity: 5,5 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 36 months/ 3000 hours

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.