

NEW HOLLAND WHEELED EXCAVATORS

MH/WE WE210 CNH 667TA/MEE TIER 3A

(2008-2012)



ENGINE CNH 667TA/MEE
Capacity: 16 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

DIFFERENTIAL FRONT
Capacity: 12,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR
Capacity: 12 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT
Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS REAR
Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT
Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM
Capacity: 330 liter (Hydraulic system including tank)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Perlus H 68

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
MoS2 Grease EP 2

NEW HOLLAND WHEELED EXCAVATORS

MH/WE WE210 CNH 667TA/MEE TIER 3A

(2008-2012)



SLEWING RING GEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 29 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

SWING REDUCTION UNIT

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.