## NEW HOLLAND TRACKED EXCAVATORS E E265 LC CNH F4AE0684L\*D101 TIER 2 (2005-2007)



| ENGINE CNH F4AE0684L<br>Capacity: 17 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal                                     |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40                      | Agridiesel CRD+ 15W-40   | Dieselfleet CD+ 15W-40   |
| Change every 500 hours                     |                          |                          |
| USE  |                          | CLIMATE                  |
| Initial service                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40                      | Agridiesel CRD+ 15W-40   | Dieselfleet CD+ 15W-40   |

Change every 50 hours

| TRAVEL REDUCTION UNITS<br>Capacity: 3,5 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal  |                             | Moderate |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                          | Unigear HS GL-3/GL-5 80W-90 |          |
|   |                             |          |

Change every 2000 hours

| HYDRAULIC SYSTEM<br>Capacity: 180 liter (Tank), Capacity: 280 liter (Total) |                          |          |  |
|---|--------------------------|----------|--|
| USE   |                          | CLIMATE  |  |
| Normal  |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |  |
| Perlus Biosynth 46  | Perlus H 46              |          |  |
| Change every 2500 hours   | · · ·                    | ·        |  |

Change every 2500 hours

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2  | Q5 MP Calcep Grease EP 2 |

## NEW HOLLAND TRACKED EXCAVATORS E E265 LC CNH F4AE0684L\*D101 TIER 2 (2005-2007)



| COOLING SYSTEM<br>Capacity: 23 liter |                          |          |
|--------------------------------------|--------------------------|----------|
| USE                                  |                          | CLIMATE  |
| Normal                               |                          | Moderate |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15+                       | Coolant SP 12            |          |
|                                      | 1                        |          |

Change every 2000 hours

| SWING GEAR               |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| MoS2 Grease EP 2         |          |

| SWING REDUCTION UNIT<br>Capacity: 15,3 liter |                             |          |
|--|-----------------------------|----------|
| USE  |                             | CLIMATE  |
| Normal                                       |                             | Moderate |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                         | Unigear HS GL-3/GL-5 80W-90 |          |
| Change every 1000 hours                      |                             |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.