## NEW HOLLAND TRACKED EXCAVATORS E E305B LC CNH 667TA/EEA TIER 3A (2008-2011)



| ENGINE CNH 667TA/EEA<br>Capacity: 18,3 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal                                       |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40                        | Agridiesel CRD+ 15W-40   | Dieselfleet CD+ 15W-40   |

| TRAVEL REDUCTION UNITS<br>Capacity: 5 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal                                      |                             | Moderate |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                        | Unigear HS GL-3/GL-5 80W-90 |          |

| HYDRAULIC SYSTEM<br>Capacity: 172 liter (Tank), Capacity: 280 liter (Total) |                          |          |  |
|---|--------------------------|----------|--|
| USE   |                          | CLIMATE  |  |
| Normal  |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |  |
| Perlus H 46   | Perlus AF 46             |          |  |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2  | Q5 MP Calcep Grease EP 2 |

| COOLING SYSTEM<br>Capacity: 25 liter |                          |          |   |
|--------------------------------------|--------------------------|----------|---|
| USE                                  |                          | CLIMATE  |   |
| Normal                               |                          | Moderate |   |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 |          |   |
| Coolant SP 15+                       | Coolant SP 12            |          |   |
|                                      |                          |          | - |

## NEW HOLLAND TRACKED EXCAVATORS E E305B LC CNH 667TA/EEA TIER 3A (2008-2011)



| SWING GEAR               |  |          |
|--------------------------|--|----------|
| USE                      |  | CLIMATE  |
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| MoS2 Grease EP 2         |  |          |

| SWING REDUCTION UNIT<br>Capacity: 7,4 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal                                      |                             | Moderate |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                        | Unigear HS GL-3/GL-5 80W-90 |          |
|   | 1                           | 1        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.