NEW HOLLAND TRACKED EXCAVATORS E E485 BEH ISUZU AA-6SD1XQY TIER 2 (2004-2007)



| | CLIMATE |
|--------------------------|--------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |
| | |

Change every 500 hours

| TRAVEL REDUCTION UNITS Capacity: 11 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 2000 hours

| HYDRAULIC SYSTEM Capacity: 220 liter (Tank), Capacity: 300 liter (Total) | | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Perlus H 46 | Perlus AF 46 | | |
| | | | |

Change every 2500 hours

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2 | Q5 MP Calcep Grease EP 2 |

| COOLING SYSTEM Capacity: 36 liter (Total) | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15+ | Coolant SP 12 | | |
| Change every 2000 hours | | | |

NEW HOLLAND TRACKED EXCAVATORS E E485 BEH ISUZU AA-6SD1XQY TIER 2 (2004-2007)



| SWING GEAR | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| MoS2 Grease EP 2 | |

| SWING REDUCTION UNIT Capacity: 21,5 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 1000 hours | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.