PRODUCT RECOMMENDATION

NEW HOLLAND WHEELED LOADERS LW/W W170 TC CNH F4HE0684J EU STAGE 2 / TIER 2 (2005-2007)

ENGINE CNH F4HE0684J
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

DIFFERENTIAL FRONT
Capacity: 32 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 1000 hours

DIFFERENTIAL REAR
Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 1000 hours

TRANSMISSION POWERSHIFT 4/3
Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 109 liter (Tank), Capacity: 193 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus H 46**	

Change every 2000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

NEW HOLLAND WHEELED LOADERS LW/W W170 TC CNH F4HE0684J EU STAGE 2 / TIER 2 (2005-2007)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 26 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	
Change every 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367