

# NEW HOLLAND MINI EXCAVATORS

## E/EC/EH EC45 MITSUBISHI S4Q2 (1999-2003)

**ENGINE** Mitsubishi S4Q2

Capacity: 5,5 liter, Filter capacity: 1 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Kroontrak MTH 10W-30</b> |  |          |

**HYDRAULIC SYSTEM**

Capacity: 102 liter, Capacity: 72 liter (Hydraulic tank)

| USE                      |                             | CLIMATE                  |
|--------------------------|-----------------------------|--------------------------|
| Normal                   |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

**GREASE POINTS/NIPPLES**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

**COOLING SYSTEM**

Capacity: 10 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

**TRAVEL REDUCTION UNIT**

Capacity: 0,9 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gearlube LS 80W-90</b> |  |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.