## PALFINGER LOADER CRANES PK 3400 PERFORMANCE



| HYDRAULIC SYSTEM   |                          |                          |  |
|--|--------------------------|--------------------------|--|
| USE  |                          | CLIMATE                  |  |
| Normal   |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1                                 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |
| Perlus H 46  | Perlus H 32              | Perlus AF 46             |  |
| Check every 50 hours, change every 1000 hours/ 12 months |                          |                          |  |
| USE  |                          | CLIMATE                  |  |
| Biodegradable oil  |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1                                 | PRODUCT RECOMMENDATION 2 |                          |  |
| Perlus Biosynth 46                                       | Perlus Biosynth 32       |                          |  |

Check every 50 hours, change every 1000 hours/ 12 months

| GREASE POINTS/NIPPLES           |                          |                          |
|---------------------------------|--------------------------|--------------------------|
| USE                             |                          | CLIMATE                  |
| Normal                          |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q11 Xtreme Duty Grease EP 2     | Q7 MP Calcep Grease WR 2 | Caliplex HD Grease EP 2  |
| Change every 3 months/ 50 hours | 1                        |                          |

 WINCH
 CLIMATE

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2

 PRODUCT RECOMMENDATION 1
 Gearlube GL-5 80W-90

 Unigear HS GL-3/GL-5 80W-90
 Unigear HS GL-3/GL-5 80W-90

Check every 50 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.