PISTENBULLY PISTENBULLY PB 600 STANDARD



ENGINE Mercedez-Benz OM460LA Tier III Capacity: 39,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrisynth LSP 10W-40	Armado Synth 10W-40		

Change every 600 hours/ 12 months

FINAL REDUCTION		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Abacot MEP Synth 220
Change every 800 hours/ 12 month	78	'

TRANSFERBOX Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Abacot MEP Synth 220

Change every 800 hours/ 12 months

TRANSMISSION/HYDRAULIC SYSTEM Capacity: 100 liter (System)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 1200 hours/ 12 months	

Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
GREASE POINTS/NIPPLES GENERAL			

PISTENBULLY PISTENBULLY PB 600 STANDARD



COOLING SYSTEM Capacity: 36 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change every 36 months/ 3600 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.