SANDERSON ROUGH TERRAIN FORKLIFT TRUCKS 264 - 4WD



ENGINE Perkins 4.236		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 250 hours

DIFFERENTIAL FRONT Ford		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 1000 hours/ 12 months		

DIFFERENTIAL REAR USE CLIMATE Normal Tropical **PRODUCT RECOMMENDATION 1** PRODUCT RECOMMENDATION 2 Gearlube GL-5 85W-140 Unigear LS GL-3/GL-5 85W-140 Change every 1000 hours/ 12 months USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gearlube GL-5 80W-90 Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT Ford		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 1000 hours/ 12 months		

SANDERSON ROUGH TERRAIN FORKLIFT TRUCKS 264 - 4WD



HUB REDUCTIONS REAR			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140		
Change every 1000 hours/ 12 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		

Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours/ 12 months

Gearlube GL-5 80W-90

TRANSMISSION PowerShuttle/Spicer Compact		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	
Change every 750 hours		

HYDRAULIC SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 1000 hours/ 12 months	·	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SANDERSON ROUGH TERRAIN FORKLIFT TRUCKS 264 - 4WD



LIFT CHAINS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Industrial Chain Spray		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.