

# SKYJACK TELEHANDLERS ZB10044

## CUMMINS QSB4.5-T (85300001 - 85399999)



**ENGINE** Cummins QSB4.5T  
Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	

*Check every 8 hours, change every 3 months/ 250 hours*

### DIFFERENTIAL FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours/ 12 months*

### DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours/ 12 months*

### HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 3 months/ 250 hours*

### HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 3 months/ 250 hours*

# SKYJACK TELEHANDLERS ZB10044

## CUMMINS QSB4.5-T (85300001 - 85399999)

**TRANSMISSION POWERSHIFT** Dana T20000 3/3

Capacity: 24 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

*Change every 1000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 155 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Check every 8 hours, change every 12 months/ 1000 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 40 hours***GREASE POINTS/NIPPLES BOOM SLIDE BEARINGS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Aluplex FGS Grease EP 2</b>		

*Change every 40 hours***COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 8 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.