## SKYJACK TELEHANDLERS ZB6042 CUMMINS 4BT4.5 (B6042T217950A -B6042T233680G)



| ENGINE Cummins 4BT4.5    |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Multifleet SHPD 15W-40   |          |
|                          |          |

Check every 8 hours, change every 3 months/ 250 hours

| DIFFERENTIAL FRONT                 |  |          |
|------------------------------------|--|----------|
| USE                                |  | CLIMATE  |
| Normal                             |  | Moderate |
| PRODUCT RECOMMENDATION 1           |  |          |
| Gearlube LS 80W-90                 |  |          |
| Change avenu 1000 hours/ 12 months |  |          |

Change every 1000 hours/ 12 months

| DIFFERENTIAL REAR                  |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Gearlube LS 80W-90                 |          |
| Change every 1000 hours/ 12 months | I        |

| HUB REDUCTIONS FRONT     |  |          |  |
|--------------------------|--|----------|--|
| USE                      |  | CLIMATE  |  |
| Normal                   |  | Moderate |  |
| PRODUCT RECOMMENDATION 1 |  |          |  |
| Gearlube LS 80W-90       |  |          |  |
|                          |  |          |  |

Change every 1000 hours/ 12 months

| HUB REDUCTIONS REAR                |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Gearlube LS 80W-90                 |          |
| Change every 1000 hours/ 12 months |          |

## SKYJACK TELEHANDLERS ZB6042 CUMMINS 4BT4.5 (B6042T217950A -B6042T233680G)



| TRANSMISSION POWERSHIFT Dana T12000 3/3<br>Capacity: 16 liter |                          |          |  |
|---|--------------------------|----------|--|
| USE   |                          | CLIMATE  |  |
| Normal  |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                                      | PRODUCT RECOMMENDATION 2 |          |  |
| SP Matic 2032   | ATF Almirol              |          |  |
|   |                          |          |  |

Change every 1000 hours/ 12 months

| HYDRAULIC SYSTEM<br>Capacity: 140 liter |          |
|---|----------|
| USE                                     | CLIMATE  |
| Normal                                  | Moderate |
| PRODUCT RECOMMENDATION 1                |          |
| Perlus H 32                             |          |
| Change over 1000 hours / 12 months      |          |

Change every 1000 hours/ 12 months

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| GREASE POINTS/NIPPLES BOOM SLIDE BEARINGS |          |  |
|---|----------|--|
| USE                                       | CLIMATE  |  |
| Normal                                    | Moderate |  |
| PRODUCT RECOMMENDATION 1                  |          |  |
| Aluplex FGS Grease EP 2                   |          |  |

| COOLING SYSTEM           |                          |          |
|--------------------------|--------------------------|----------|
| USE                      |                          | CLIMATE  |
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Coolant -38 Organic NF   | Coolant -26              |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.