

# SMV FORKLIFT TRUCKS SL 12-1200 A (1995-2006)



**ENGINE** Scania DSI 9  
Capacity: 20-25 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel MSP 15W-40**

## PRODUCT RECOMMENDATION 2

**Agridiesel CRD+ 15W-40**

## PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30***Change every 250 hours***DIFFERENTIAL**

Capacity: 20 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube HS GL-5 80W-140***Check every 250 hours, change every 2000 hours***GEARBOX**

Capacity: 21 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 1000 hours*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W**

## PRODUCT RECOMMENDATION 2

**ATF Dexron II-D***Change every 1000 hours***HUB REDUCTIONS**

Capacity: 7 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube HS GL-5 80W-140***Check every 250 hours, change every 2000 hours***HYDRAULIC SYSTEM**

Capacity: 175 liter (Hydraulic tank)

We are unable to give a standard recommendation for this component. Please contact our service department.

# SMV FORKLIFT TRUCKS SL 12-1200 A (1995-2006)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 50 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.