

# SNORKEL/UPRIGHT AB SERIES AB46E I/C

## KUBOTA WG750

**ENGINE** Kubota WG750

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Asyntho 5W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>
<i>Change every 100 hours</i>		

**HUB REDUCTIONS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	
<i>Change every 500 hours</i>		

**HYDRAULIC SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		
<i>Change every 500 hours</i>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Perlus H 15</b>		
<i>Change every 500 hours</i>		

**GREASE POINTS/NIPPLES SWING BEARING**

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	

# SNORKEL/UPRIGHT AB SERIES AB46E I/C KUBOTA WG750



## SWING REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 500 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*