

# STILL PLATFORM TRUCKS & TRACTORS, ELECTRIC R07-25L



## DIFFERENTIAL

| USE                           |                                  | CLIMATE                  |
|-------------------------------|----------------------------------|--------------------------|
| Normal                        |                                  | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3 |
| <b>Kroontrak CVT 10W-40</b>   | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |
| <i>Change every 600 hours</i> |                                  |                          |

## HYDRAULIC SYSTEM

| USE                            |                          | CLIMATE                  |
|--------------------------------|--------------------------|--------------------------|
| Normal                         |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus Biosynth 46</b>      | <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |
| <i>Change every 1000 hours</i> |                          |                          |

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.