SVEDALA DEMAG TRACKED PAVERS DF145C TYPE 438/439 (2001 AND AFTER)



ENGINE Cummins QSB6.7		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 500 hours

PUMP REDUCTION UNIT Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
	· · · · · · · · · · · · · · · · · · ·	

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 240 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 10 hours, change every 2000	hours/24 months	
USE		CLIMATE
Biodegradable oil		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 2000	hours/ 24 months	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant -38 Organic NF	Coolant -26	Coolant -33 MPG

SVEDALA DEMAG TRACKED PAVERS DF145C TYPE 438/439 (2001 AND AFTER)



AUGER BOX Capacity: 5,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP 460	
Check every 100 hours, change every 100	ours/ 12 months

AUGER REDUCTION UNIT Capacity: 0,5 liter	
use Normal	CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Abacot MEP 220	

Check every 100 hours, change every 1000 hours/ 12 months

CONVEYOR GEARBOX Capacity: 0,5 liter (each side)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP 220	
011	

Check every 50 hours, change every 1000 hours/ 12 months

е

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.