SVETRUCK LIFT TRUCKS 45120-57 SCANIA



PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

ENGINE Scania DC12		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30
Check every 10 hours, change every 2 months/ 400 hours		
USE		CLIMATE
Initial service		Moderate

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

Change every 50 hours

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

Change every 5 months/ 1000 hours

DIFFERENTIAL FRONT		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
Change every 5 months/ 1000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

TRANSMISSION ZF ErgoPower 4/3		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT

Check every 10 hours, change every 5 months/ 1000 hours

HYDRAULIC SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		
Check every 10 hours, change every 10 months/ 2000 hours			

SVETRUCK LIFT TRUCKS 45120-57 SCANIA



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM ENGINE			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

COOLING SYSTEM HYDRAULIC BRAKES NO SEPERATE TANK		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 10 hours		,

COOLING SYSTEM HYDRAULIC BRAKES WITH SEPERATE TANK		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 10 hours	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.