WINCH BRAKE Capacity: 0,9 liter

TADANO FAUN TRUCK CRANES TS-300B-1, CRANE WITHOUT CARRIER



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 22	Perlus H 15	Perlus AF 32
Change every 2000 hours/ 24 months		
HYDRAULIC SYSTEM Capacity: 470 liter (System), Capacity: 32	7 liter (Tank)	
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 2000 hours/ 24 months		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 2000 hours/ 24 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours/ 24 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		
Change every 2000 hours/ 24 months		
LIGE		01.014.75

Initial service

Perlus H 68

PRODUCT RECOMMENDATION 1

Change every 250 hours/3 months

Tropical

TADANO FAUN TRUCK CRANES TS-300B-1, CRANE WITHOUT CARRIER



use Initial service	climate Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 250 hours/ 3 months	
USE	CLIMATE
Initial service	Cold
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 250 hours/ 3 months	
USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1	
Perlus H 22	
Change every 250 hours/ 3 months	

GREASE POINTS/NIPPLES GENE	RAL	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Unigear LS GL-3/GL-5 85W-140	Abacot MEP 320
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Unigear LS GL-3/GL-5 85W-140	Abacot MEP 320
	,
	Unigear LS GL-3/GL-5 85W-140 PRODUCT RECOMMENDATION 2

SWING REDUCTION GEAR

Capacity: 1,6 liter

TADANO FAUN TRUCK CRANES TS-300B-1, CRANE WITHOUT CARRIER



WINCH REDUCTION GEAR Capacity: 2 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours/ 12 month	ns	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 250 hours/ 3 months		•

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.