

# TADANO FAUN ROUGH TERRAIN CRANES

## TR-200EXC-3 MITSUBISHI 6D16-T



**ENGINE** Mitsubishi 6D16-T  
Capacity: 20 liter, Filter capacity: 4 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W****DIFFERENTIALS**

Capacity: 14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 2000 hours/ 24 months***HUB REDUCTIONS**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 2000 hours/ 24 months*

# TADANO FAUN ROUGH TERRAIN CRANES

## TR-200EXC-3 MITSUBISHI 6D16-T

**TORQUE CONVERTER 4/1**

Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Change every 1000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 300 liter (Tank), Capacity: 410 liter (Total)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68***Change every 2000 hours/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 2000 hours/ 24 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68***Change every 250 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 250 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

# TADANO FAUN ROUGH TERRAIN CRANES

## TR-200EXC-3 MITSUBISHI 6D16-T



### SPEED REDUCER WINCH

Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Abacot MEP 320**

Change every 1000 hours/ 12 months

### SWING BRAKE UNIT

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Abacot MEP 320**

### WIRE ROPES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Compound OGL**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.