

TAKEUCHI TRACKED EXCAVATORS TB

TB007 -> S/N 1074339

**ENGINE** Yanmar 2TN66L-UTBZ

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 40	HDX 40

Change every 250 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40	HDX 30

Change every 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30	HDX 20W-20

Change every 250 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
HDX 10W	

Change every 250 hours

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 40	HDX 40

Change every 50 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40	HDX 30

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30	HDX 20W-20

Change every 50 hours

TAKEUCHI TRACKED EXCAVATORS TB

TB007 -> S/N 1074339



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
<i>Change every 50 hours</i>		

HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
<i>Change every 1000 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Change every 10 hours</i>		

SLEW GEARS & PINION		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Change every 500 hours</i>		

PUMP SLINE SECTION		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

TAKEUCHI TRACKED EXCAVATORS TB

TB007 -> S/N 1074339



SLEW REDUCTION GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 500 hours

TRACK DRIVE GEARBOXES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.