TAKEUCHI TRACKED EXCAVATORS TB TB135 (TILL 2008)



ENGINE Yanmar 3TNE88-TB Capacity: 4,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 250 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 50 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 50 hours		
	5 litar (Tatal)	
HYDRAULIC SYSTEM Capacity: 48 liter (Tank), Capacity: 89	5 liter (Total)	CLIMATE
Capacity: 48 liter (Tank), Capacity: 85 use	5 liter (Total)	сымате Mediterranean
Capacity: 48 liter (Tank), Capacity: 89 use Normal		climate Mediterranean
	PRODUCT RECOMMENDATION 2 Perlus H 68	
Capacity: 48 liter (Tank), Capacity: 85 USE Normal PRODUCT RECOMMENDATION 1 Perlus H 46	PRODUCT RECOMMENDATION 2	
Capacity: 48 liter (Tank), Capacity: 89 USE Normal PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

PRODUCT RECOMMENDATION 1

Change every 2000 hours

Perlus H 32

TAKEUCHI TRACKED EXCAVATORS TB TB135 (TILL 2008)



GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Change every 50 hours				

COOLING SYSTEM Capacity: 5,4 liter				
use Normal		сцімате Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			
Change every 1000 hours	'			

TRAVEL REDUCTION GEARBOX Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours		•
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 250 hours		·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.