

TAKEUCHI TRACKED EXCAVATORS TB

TB138FR YANMAR 3TNV88-XTBZ (13810003->)



ENGINE Yanmar 3TNV88
Capacity: 4,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Check every 8 hours, change every 250 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 41 liter (Hydraulic tank), Capacity: 68 liter (System)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Perlus H 46

PRODUCT RECOMMENDATION 2
Perlus H 68

Check every 8 hours, change every 2000 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 32

Check every 8 hours, change every 2000 hours

COOLING SYSTEM

Capacity: 5,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2
Coolant -26

Check every 8 hours, change every 1000 hours

TAKEUCHI TRACKED EXCAVATORS TB

TB138FR YANMAR 3TNV88-XTBZ (13810003->)



LEVERS & PEDAL

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SLEW BEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

TRAVEL REDUCTION GEARBOX

Capacity: 0,6 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours

WORKING EQUIPMENT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 10 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.