TCM FORKLIFT & REACH TRUCKS, DIESEL FD80Z7



| ENGINE Isuzu 6BD1 | | |
|-----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| Change every 600 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| Change every 600 hours/ 12 months | • | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| Change every 600 hours/ 12 months | | |

| DIFFERENTIAL | | |
|--------------------------|-----------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1200 hours/ 12 months

| use Normal | | climate Moderate |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | SP Gear 1081 | SP Gear 5015 |

Change every 1200 hours/ 12 months

| TRANSMISSION Powershift | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 2032 | |
| Change every 1200 hours/ 12 months | |

TCM FORKLIFT & REACH TRUCKS, DIESEL FD80Z7



PRODUCT RECOMMENDATION 3

SP Gear 5015

| TRANSMISSION MANUAL | | |
|------------------------------------|-----------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 1200 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| | | |

PRODUCT RECOMMENDATION 2

SP Gear 1081

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

Change every 1200 hours/ 12 months

| HYDRAULIC SYSTEM | | |
|---------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 32 | Perlus H 22 | |
| Change every 1200 hours/ 12 mon | ths | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM | |
|------------------------------------|-----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| Change every 1200 hours/ 12 months | · · · · · |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

TCM FORKLIFT & REACH TRUCKS, DIESEL FD80Z7



| FINAL REDUCTION GEAR | | |
|------------------------------------|-----------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 1200 hours/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | SP Gear 1081 | SP Gear 5015 |

Change every 1200 hours/ 12 months

| STEERING GEAR | | |
|-----------------------------------|-----------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 1200 hours/ 12 month | 15 | |

| USE | |
|--------------------------|--------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1081 | SP Gear 5015 |
| | |

Change every 1200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.