TCM FORKLIFT & REACH TRUCKS, DIESEL FHD25Z



ENGINE Capacity: 6 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 8 hours, change every 200 ho	ours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 8 hours, change every 200 ho	ours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 8 hours, change every 200 ho	ours	

TCM FORKLIFT & REACH TRUCKS, DIESEL FHD25Z



N .	
	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90
00 hours	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1081	SP Gear 5015
00 hours	
	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1081	SP Gear 5015
	PRODUCT RECOMMENDATION 2 Gearlube GL-5 80W-90 On hours PRODUCT RECOMMENDATION 2 SP Gear 1081 On hours PRODUCT RECOMMENDATION 2 Gearlube GL-5 80W-90 PRODUCT RECOMMENDATION 2

Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	
Check every 200 hours, change ever	y 1200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	
Check every 200 hours, change ever	y 600 hours	•

TRANSMISSION Powershift

TCM FORKLIFT & REACH TRUCKS, DIESEL FHD25Z



TRANSMISSION MANUAL Capacity: 11 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 600 hours, change eve	ery 1200 hours		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015	
Check every 600 hours, change eve	ery 1200 hours		

HYDRAULIC SYSTEM Capacity: 37 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Perlus H 32	Perlus H 22
Check every 8 hours, change even	v 1200 hours	'

Check every 8 hours, change every 1200 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,2 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 8 hours, change every 1200 hours		

GREASE POINTS/NIPPLES USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

TCM FORKLIFT & REACH TRUCKS, DIESEL FHD25Z



COOLING SYSTEM Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 8 hours, change every	24 months/ 600 hours	

Check every 8 hours, change every 24 months/ 600 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.