

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL340 0019 -> 0032 (2005 AND AFTER)



ENGINE Deutz BF6M-2012C
Capacity: 15 liter

| USE | CLIMATE |
|----------------------------------|----------|
| Normal, fuel sulfur level <0,05% | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-----------------------------|
| Agrisynth LSP 10W-40 | Kroontrak CVT 10W-40 | Agrisynth MSP 10W-40 |

Check every 8 hours, change every 12 months/ 500 hours

HYDRAULIC SYSTEM

Capacity: 330 liter (Hydraulic tank)

| USE | CLIMATE |
|----------------|---------------|
| Flexible (max) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus AF 46 | | |

Change every 3000 hours/ 12 months

| USE | CLIMATE |
|----------------|----------|
| Flexible (max) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---------------------------|--------------------------|--|
| Perlus Biosynth 46 | Perlus H 46 | |

Change every 3000 hours/ 12 months

| USE | CLIMATE |
|-----------------------------|---------------|
| Alternative, flexible (max) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Perlus Biosynth 46 | | |

Change every 3000 hours/ 12 months

GREASE POINTS/NIPPLES CENTRAL LUBRICATING SYSTEM

Capacity: 3 kg

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------------|--|--|
| HT Q9 High Grade Grease | | |

GREASE POINTS/NIPPLES OTHERS

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------------|--|--|
| HT Q9 High Grade Grease | | |

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL340 0019 -> 0032 (2005 AND AFTER)



GREASE POINTS/NIPPLES SWING RING GEAR

Capacity: 21 kg

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 40 liter

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| <i>Change every 24 months</i> | | |

GRAB GEAR UNIT

Capacity: 0,7 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

TRAVEL REDUCTION UNIT

Capacity: 5 liter

| USE | | CLIMATE |
|---|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| <i>Change every 1000 hours/ 12 months</i> | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| <i>Change every 100 hours</i> | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.