

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL860D 860050/0016 -> 0018 (2011 AND AFTER)



HYDRAULIC SYSTEM

Capacity: 520 liter (Hydraulic tank)

USE	CLIMATE
Flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus AF 46*Change every 3000 hours/ 12 months*

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

PRODUCT RECOMMENDATION 2

Perlus H 46*Change every 3000 hours/ 12 months*

USE	CLIMATE
Alternative, flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Change every 3000 hours/ 12 months*

GREASE POINTS/NIPPLES CENTRAL LUBRICATING SYSTEM

Capacity: 4 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

SWING REDUCTION UNIT

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 500 hours/ 12 months*

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL860D 860050/0016 -> 0018 (2011 AND AFTER)

**TRAVEL REDUCTION UNIT**

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.