

TEREX O&K HYDRAULIC EXCAVATORS RH 90C DHT CATERPILLAR C18 (X2)

**ENGINE C18**

Capacity: 64 liter (each engine)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40*Check every 10 hours, change every 6 months/ 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 5W-30

PRODUCT RECOMMENDATION 2

Dieselfleet LSP Ultra 10W-30*Check every 10 hours, change every 6 months/ 250 hours***HYDRAULIC SYSTEM**

Capacity: 2000 liter (Hydraulic tank), Capacity: 2500 liter (Total system volume)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 68*Check every 10 hours, change every 36 months/ 5000 hours***GREASE POINTS/NIPPLES AUTOMATIC LUBRICATION SYSTEM**

Capacity: 180-500 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2*Check every 10 hours***COOLING SYSTEM**

Capacity: 85 liter (each engine)

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 10 hours, change every 72 months/ 12000 hours*

TEREX O&K HYDRAULIC EXCAVATORS RH 90C DHT CATERPILLAR C18 (X2)



PUMP TRANSFER GEARBOX

Capacity: 19 liter (each (2x))

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	

Check every 60 hours, change every 1000 hours

SWING DRIVE GEARBOX

Capacity: 22 liter (each (2x))

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Abacot MEP 320		

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	

Check every 10 hours, change every 1000 hours

TRAVEL REDUCTION UNIT

Capacity: 25 liter (each (2x))

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Abacot MEP Synth 220	Abacot MEP 220	

Check every 500 hours, change every 36 months/ 5000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.