

# TEREX WHEELED EXCAVATORS HML23

## 2300/0099-> (2003-2006)



**ENGINE** Deutz F4M-2011  
Capacity: 10 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Armado Synth 5W-30**

*Check every 10 hours, change every 1000 hours/ 12 months*

### DIFFERENTIAL FRONT

Capacity: 3,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Change every 100 hours*

# TEREX WHEELED EXCAVATORS HML23

## 2300/0099-> (2003-2006)

**DIFFERENTIAL REAR**

Capacity: 4,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 100 hours***HUB REDUCTIONS FRONT**

Capacity: 0,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 100 hours***HUB REDUCTIONS REAR**

Capacity: 0,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 50 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 100 hours*

# TEREX WHEELED EXCAVATORS HML23

## 2300/0099-> (2003-2006)

**TRANSFERBOX**

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 100 hours***HYDRAULIC SYSTEM**

Capacity: 180 liter, Capacity: 110 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 68***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus H 46**

PRODUCT RECOMMENDATION 3

**Perlus Biosynth 32***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus Biosynth 32***Check every 500 hours, change every 1000 hours/ 12 months***GREASE POINTS/NIPPLES**

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*