PRODUCT RECOMMENDATION

TEREX TRACKED EXCAVATORS TC10
TC10SR0151-> (2012 AND AFTER)

ENGINE Yanmar 2TNV70
Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

Check every 10 hours, change every 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

Change every 100 hours

HYDRAULIC SYSTEM
Capacity: 20 liter (Hydraulic tank), Capacity: 10 liter (System)

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**
Perlus Biosynth 46	**Perlus H 46**

Check every 10 hours, change every 1000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**
Q5 MP Calcep Grease EP 2	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 10 hours, change every 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TEREX TRACKED EXCAVATORS TC10
TC10SR0151-> (2012 AND AFTER)

TRAVEL REDUCTION UNIT Capacity: 0,06 liter (each)		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube GL-5 80W-90**	PRODUCT RECOMMENDATION 2 **Unigear HS GL-3/GL-5 80W-90**	
Check every 250 hours, change every 1000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367