

# TEREX TRACKED EXCAVATORS TC240

## (2006 AND AFTER)



**ENGINE** Cummins QSB6.7  
Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>

*Check every 10 hours, change every 500 hours/ 6 months*

**HYDRAULIC SYSTEM**  
Capacity: 216 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

*Check every 10 hours, change every 24 months/ 3000 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Check every 10 hours, change every 24 months/ 3000 hours*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

*Check every 10 hours, change every 50 hours*

### GREASE POINTS/NIPPLES SWING GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Compound OGL EP 0/1</b>		

*Change every 100 hours*

# TEREX TRACKED EXCAVATORS TC240

## (2006 AND AFTER)

**COOLING SYSTEM**

Capacity: 42 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 10 hours, change every 2000 hours/ 24 months*

**SWING REDUCTION UNIT**

Capacity: 6 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Check every 100 hours, change every 1000 hours/ 12 months*

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 100 hours, change every 1000 hours/ 12 months*

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 50 hours*

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 50 hours*

# TEREX TRACKED EXCAVATORS TC240

## (2006 AND AFTER)

**TRAVEL REDUCTION UNIT**

Capacity: 6 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Check every 100 hours, change every 12 months/ 2000 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 100 hours, change every 12 months/ 2000 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Check every 50 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 50 hours, change every 500 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.