PRODUCT RECOMMENDATION

TEREX TRACKED EXCAVATORS TC25 TIER 4 0101 -> (2008 AND AFTER)

ENGINE Mitsubishi S3L2
Capacity: 5,7 liter (Change capacity)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	**Multifleet SHPD 10W-40**	

Check every 10 hours, change every 500 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**

Change every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	**Multifleet SHPD 10W-40**	

Change every 100 hours

HYDRAULIC SYSTEM
Capacity: 34 liter (Hydraulic tank), Capacity: 40 liter (Total)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 500 hours, change every 12 months/ 1500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	**Perlus H 46**	**Perlus Biosynth 32**

Check every 500 hours, change every 12 months/ 1500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TEREX TRACKED EXCAVATORS TC25 TIER 4 0101 -> (2008 AND AFTER)

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	**Perlus H 46**	**Perlus Biosynth 32**

Check every 100 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus Biosynth 32**	

Check every 50 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service, biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus Biosynth 32**	

Check every 100 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 100 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TEREX TRACKED EXCAVATORS TC25 TIER 4 0101 -> (2008 AND AFTER)

COOLING SYSTEM
Capacity: 4,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 1000 hours/ 12 months

TRAVEL REDUCTION UNIT
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 12 months/ 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367