

TEREX WHEELED LOADERS TL260 0101- >0134 (2006-2008)



ENGINE Perkins 1106C-E60TA
Capacity: 15 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Armado Synth 5W-30

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 500 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 100 hours

TEREX WHEELED LOADERS TL260 0101- >0134 (2006-2008)

**DIFFERENTIAL REAR**

Capacity: 14,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 100 hours***HUB REDUCTIONS FRONT**

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 100 hours***HUB REDUCTIONS REAR**

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 100 hours*

TEREX WHEELED LOADERS TL260 0101- >0134 (2006-2008)

**TRANSMISSION**

Capacity: 4,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

Check every 500 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

*Change every 100 hours***HYDRAULIC SYSTEM**

Capacity: 95 liter (Change capacity), Capacity: 135 liter (Total)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 500 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32

Check every 500 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32

Check every 100 hours

TEREX WHEELED LOADERS TL260 0101- >0134 (2006-2008)



USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus Biosynth 32	

Check every 500 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service, biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus Biosynth 32	

Check every 100 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 100 hours

COOLING SYSTEM

Capacity: 41 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.