

# TEREX ARTICULATED DUMP TRUCKS TA30 (TILL 2008)

**ENGINE** Cummins LTA10-C275

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 250 hours/ 1 months*

**ENGINE** Cummins MTA11-C300

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 250 hours/ 1 months*

**DIFFERENTIAL AXLE 1**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours/ 6 months*

**DIFFERENTIAL AXLE 2**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours/ 6 months*

**DIFFERENTIAL AXLE 3**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours/ 6 months*

# TEREX ARTICULATED DUMP TRUCKS TA30 (TILL 2008)



## HUB REDUCTIONS AXLE 1

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		
<i>Change every 1000 hours/ 6 months</i>		

## HUB REDUCTIONS AXLE 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		
<i>Change every 1000 hours/ 6 months</i>		

## HUB REDUCTIONS AXLE 3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		
<i>Change every 1000 hours/ 6 months</i>		

## TRANSMISSION ZF 6WG260 6/3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Change every 1000 hours/ 6 months</i>		

## HYDRAULIC SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*