

## TEREX MINI DUMPERS HD1200



**ENGINE** Kubota D905  
Capacity: 3,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 250 hours*

**HYDRAULIC SYSTEM**  
Capacity: 25,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 46**

*Check every 10 hours, change every 500 hours*

**GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

*Change every 10 hours*

**COOLING SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

*Check every 10 hours, change every 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.