## **TEREX MINI DUMPERS PT3500H** (2004-2010)



ENGINE Kubota V2203 Capacity: 9,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 250 l	nours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every 250 l	nours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40
Check every 10 hours, change every 250 l	nours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 250 l	nours	
DIFFERENTIAL FRONT Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate

Check eve	ry 250	hours,	change	every	500	hours

**PRODUCT RECOMMENDATION 1** 

Kroontrak MTH 10W-30

DIFFERENTIAL REAR Capacity: 7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Kroontrak MTH 10W-30	Agrifluid HT		
Charles war 250 hours about 500 hours			

**PRODUCT RECOMMENDATION 2** 

**Agrifluid HT** 

Check every 250 hours, change every 500 hours

## **TEREX MINI DUMPERS PT3500H** (2004-2010)



HYDRAULIC SYSTEM Capacity: 37 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check evenu 10 hours, change evenu 500 hours		

Check every 10 hours, change every 500 hours

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 46			
Check avery 10 hours change every 500 hours			

Check every 10 hours, change every 500 hours

GREASE POINTS/NIPPLES CENTRE PIVOT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

Change every 50 hours

GREASE POINTS/NIPPLES OTHERS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Change every 50 hours

COOLING SYSTEM Capacity: 9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check even 10 hours, change even 12 menths			

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.