

# TEREX MINI DUMPERS TA3SH (2012 AND AFTER)



<b>ENGINE</b> Kubota V2203-M Capacity: 9,5 liter		
<b>USE</b> Normal		<b>CLIMATE</b> Moderate
<b>PRODUCT RECOMMENDATION 1</b> <b>Agridiesel CRD+ 15W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Dieselfleet CD+ 15W-40</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Multifleet SHPD 15W-40</b>
<i>Check every 10 hours, change every 200 hours</i>		

<b>DIFFERENTIAL FRONT</b> Dana Capacity: 4,7 liter		
<b>USE</b> Normal		<b>CLIMATE</b> Moderate
<b>PRODUCT RECOMMENDATION 1</b> <b>Kroontrak CVT 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrifluid Synth XHP Ultra</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agrifluid HT-Plus</b>
<i>Check every 200 hours, change every 400 hours</i>		

<b>DIFFERENTIAL REAR</b> Dana Capacity: 4,7 liter		
<b>USE</b> Normal		<b>CLIMATE</b> Moderate
<b>PRODUCT RECOMMENDATION 1</b> <b>Kroontrak CVT 10W-40</b>	<b>PRODUCT RECOMMENDATION 2</b> <b>Agrifluid Synth XHP Ultra</b>	<b>PRODUCT RECOMMENDATION 3</b> <b>Agrifluid HT-Plus</b>
<i>Check every 200 hours, change every 400 hours</i>		

<b>TRANSFERBOX</b> Dana Capacity: 0,35 liter		
<b>USE</b> Normal		<b>CLIMATE</b> Moderate
<b>PRODUCT RECOMMENDATION 1</b> <b>Gear Oil Alcat 10W</b>		
<i>Check every 200 hours, change every 400 hours</i>		

<b>HYDRAULIC SYSTEM</b> Capacity: 37 liter (Hydraulic tank)		
<b>USE</b> Normal		<b>CLIMATE</b> Moderate
<b>PRODUCT RECOMMENDATION 1</b> <b>Perlus H 46</b>		
<i>Check every 10 hours, change every 400 hours</i>		

# TEREX MINI DUMPERS TA3SH (2012 AND AFTER)



## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 800 hours*

## GREASE POINTS/NIPPLES CENTRE PIVOT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	

*Check every 50 hours*

## GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

## COOLING SYSTEM

Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*