PRODUCT RECOMMENDATION

# TEREX TELEHANDLERS GIROLIFT 5022
# 16758->24909 (2007 AND AFTER)

## ENGINE Perkins 1106D-E66TA
Capacity: 13,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Check every 10 hours, change every 1 months/ 250 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Change every 50 hours*

## DIFFERENTIAL FRONT
Capacity: 7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gearlube LS 80W-90** | | |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

## DIFFERENTIAL REAR
Capacity: 7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gearlube LS 80W-90** | | |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

## HUB REDUCTIONS FRONT
Capacity: 1,5 liter (each hub)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Gearlube LS 80W-90** | | |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# TEREX TELEHANDLERS GIROLIFT 5022
# 16758->24909 (2007 AND AFTER)

## HUB REDUCTIONS REAR
Capacity: 1,5 liter (each hub)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gearlube LS 80W-90** | | |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

## TRANSMISSION
Capacity: 2,2 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Gearlube LS 80W-90** | | |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

## HYDRAULIC SYSTEM

| USE | CLIMATE |
|---|---|
| Normal | Tropical |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Perlus H 68** | | |

*Check every 10 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus Biosynth 46** | **Perlus H 46** | |

*Check every 10 hours, change every 6 months/ 1000 hours*

| USE | CLIMATE |
|---|---|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Perlus H 22** | | |

*Check every 10 hours, change every 6 months/ 1000 hours*

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Check every 10 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# TEREX TELEHANDLERS GIROLIFT 5022
# 16758->24909 (2007 AND AFTER)

## GREASE POINTS/NIPPLES TELESCOPIC BOOM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **PTFE White Grease EP2** | | |

*Check every 10 hours*

## COOLING SYSTEM
Capacity: 35 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*Check every 10 hours, change every 2000 hours/ 12 months*

## SWING REDUCTION UNIT
Capacity: 2,8 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube LS 80W-90** | | |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367