## **TOYOTA FORKLIFT TRUCKS, DIESEL 02-6FDN25**



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
0		

Change every 1 months/ 170 hours

DIFFERENTIAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change avery 2000 hours/12 mont	ha	

Change every 2000 hours/ 12 months

TRANSMISSION + TORQUE CONVERTER		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 1000 hours/ 6 months		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 1000 hours/ 6 months	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
LHM +	
	'

## TOYOTA FORKLIFT TRUCKS, DIESEL 02-6FDN25



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
use Normal	CLIMATE  Arctic
	Alctic
PRODUCT RECOMMENDATION 1  LHM +	
LITTIN T	
CENTRAL HYDRAULIC POWER SYSTEM	M
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
CHAINS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	I I I I I I I I I I I I I I I I I I I
Industrial Chain Spray	
HYDRAULIC PUMP DRIVE UNIT	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

## **TOYOTA FORKLIFT TRUCKS, DIESEL 02-6FDN25**



CLIMATE
Moderate

Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
STEERING BOX			

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.