

TOYOTA FORKLIFT TRUCKS, LPG/PETROL

50-8FG25 (2007 AND AFTER)



ENGINE Toyota 4Y
Capacity: 4 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Check every 10 hours, change every 500 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL

Capacity: 5,8-6,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 2000 hours/ 12 months

TRANSMISSION

Capacity: 6 liter, Capacity: 10 liter (2 stator T/C)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 40 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM

Capacity: 33 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32

Check every 40 hours, change every 6 months/ 1000 hours

TOYOTA FORKLIFT TRUCKS, LPG/PETROL

50-8FG25 (2007 AND AFTER)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,2 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 8 hours, change every 6 months/ 1000 hours

WET BRAKE SYSTEM

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 8 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Change every 40 hours/ 1 each race

COOLING SYSTEM

Capacity: 8,1-9,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.