PRODUCT RECOMMENDATION

# TOYOTA FORKLIFT TRUCKS, LPG/PETROL
# TONERO 30 (2009 AND AFTER)

## ENGINE Toyota 4Y
Capacity: 4 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Asyntho 5W-30** | | |

*Check every 8 hours, change every 3 months/ 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Alternative (acceptable) | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Asyntho 5W-30** | **Synfleet SHPD 10W-40** | |

*Check every 8 hours, change every 6 weeks/ 250 hours*

## DIFFERENTIAL
Capacity: 8,2 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Gearlube GL-4 80W-90** | **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Check every 6 months/ 250 hours, change every 12 months/ 2000 hours*

## TRANSMISSION + TORQUE CONVERTER
Capacity: 6-10 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **ATF Dexron II-D** | | |

*Check every 40 hours, change every 12 months/ 2000 hours*

## HYDRAULIC SYSTEM
Capacity: 34 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 32** | | |

*Check every 8 hours, change every 6 months/ 1000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# TOYOTA FORKLIFT TRUCKS, LPG/PETROL TONERO 30 (2009 AND AFTER)

## HYDRAULIC BRAKE SYSTEM
Capacity: 0,2 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Drauliquid DOT 3** | | |

*Check every 8 hours, change every 6 months/ 1000 hours*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **MoS2 Grease EP 2** | | |

*Change every 40 hours/ 1 each race*

## GREASE POINTS/NIPPLES WHEEL BEARINGS

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **MoS2 Grease EP 2** | | |

*Change every 1000 hours/ 6 months*

## COOLING SYSTEM
Capacity: 9,28 liter, Capacity: 0,47 liter (Reservoir)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Coolant -38 Organic NF** | **Coolant -26** | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367