

# TOYOTA SKID STEER LOADERS 3SDK-4 (DIESEL)



## ENGINE

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 1 months/ 170 hours*

## HYDRAULIC SYSTEM HYDROSTATIC DRIVE

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**ATF-F (Ford)***Change every 1000 hours/ 6 months*

## GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**MoS2 Grease EP 2**

PRODUCT RECOMMENDATION 3

**Q5 MP Calcep Grease EP 2**

## ARM PIN SECTION

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## REDUCTION GEAR UNITS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

# TOYOTA SKID STEER LOADERS 3SDK-4 (DIESEL)



## WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>MoS2 Grease EP 2</b>	<b>Q5 MP Calcep Grease EP 2</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*