VERMEER UTILITY TRENCHERS V5800



Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
ENGINE		

Change every 50 hours

TRANSMISSION DIFFERENTIAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 50 hours		

HYDRAULIC SYSTEM HYDROSTATIC D	RIVE	
USE	CLIMATE	
Normal	Modera	ate
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 1000 hours		
USE	CLIMATE	
Initial service	Modera	ate
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 100 hours		

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
HT Q9 High Grade Grease	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.