VOLVO TRACKED EXCAVATORS EC EC130C (1997-1998)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	

Change every 250 hours/ 12 months

HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
Change avery 2000 have / 10 magetha		

Change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES EQUIPME	NT UNDERCARRIAGE		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

GREASE POINTS/NIPPLES SWING RING	EASE POINTS/NIPPLES SWING RING + GEAR TEETH		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			
Change avery 12 manths/ 1000 hours			

Change every 12 months/ 4000 hours

AUTOMATIC LUBRICATION SYSTEM Lincoln		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

VOLVO TRACKED EXCAVATORS EC EC130C (1997-1998)



	CLIMATE
	Mediterranean
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Unigear HS GL-3/GL-5 80W-90	
	Gearlube HS GL-5 80W-140 PRODUCT RECOMMENDATION 2

Change every 12 months/ 4000 hours

PUMP DRIVE GEARBOX	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 1000 hours/ 12 months	

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
		:

Change every 1000 hours/ 12 months

SWING REDUCTION GEARBOX		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140
Change every 12 months/ 4000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 12 months/ 4000 hours	1	

VOLVO TRACKED EXCAVATORS EC EC130C (1997-1998)



TRACK DRIVE GEARBOXES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140
Change every 12 months/ 4000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 12 months/ 4000 hours		·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.