VOLVO TRACKED EXCAVATORS EC EC160C (2007-2011)



| ENGINE Volvo D6E EBE3 Capacity: 25 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | Agridiesel MSP 15W-40 |

Change every 500 hours

| use Normal | | climate Mediterranean |
|--------------------------|--------------------------|--------------------------|
| | | |
| Perlus Biosynth 46 | Perlus H 46 | Perlus H 68 |
| Change every 2000 hours | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 32 | Perlus H 32 | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

| COOLING SYSTEM Capacity: 24 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |
| Change every 48 months/ 6000 hours | | |

VOLVO TRACKED EXCAVATORS EC EC160C (2007-2011)



| SWING REDUCTION UNIT Capacity: 2,6 liter | | |
|---|-----------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube HS GL-5 80W-140 | | |
| Change every 1000 hours | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 1000 hours | | |

| TRAVEL REDUCTION UNIT Capacity: 5,8 liter | |
|---|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube HS GL-5 80W-140 | |
| Change every 2000 hours | |

| USE | | CLIMATE |
|--------------------------|-----------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 2000 hours | · | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.