VOLVO TRACKED EXCAVATORS EC EC20C TIER 4I (2010-2015)



ENGINE Volvo D1.1DCAE4 Capacity: 3,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30
Check every 8 hours, change every 2	250 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30
	1	1

Change every 50 hours

HYDRAULIC SYSTEM Capacity: 15 liter (Hydraulic tank), Capacity: 25 liter (Total)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Perlus Biosynth 46	Perlus H 46	Perlus H 68	
Check every 8 hours, change every 1000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 32	Perlus H 32		
Check every 8 hours, change every 1000	Check every 8 hours, change every 1000 hours		
USE		CLIMATE	
Alternative (acceptable)		Mediterranean	
PRODUCT RECOMMENDATION 1			
Perlus Biosynth 46			
Check every 8 hours, change every 750 hours			
USE		CLIMATE	
Alternative (acceptable)		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus Biosynth 32			
Check every 8 hours, change every 750 h	ours		

VOLVO TRACKED EXCAVATORS EC EC20C TIER 4I (2010-2015)



COOLING SYSTEM Capacity: 5,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 8 hours, change every 2000 hours

TRAVEL REDUCTION UNIT Capacity: 0,33 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 85W-140	
Change every 1000 hours	

use Normal		сциате Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours	·	ŀ

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.