

# VOLVO WHEELED LOADERS L L150G

## STAGE IIIB/TIER 4I (2010-2014)



**ENGINE** Volvo D13H Stage IIIB/Tier 4i  
Capacity: 50 liter

USE	CLIMATE
Normal, fuel sulfur level < 15 ppm	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>

*Check every 8 hours, change every 500 hours*

USE	CLIMATE
Alternative, fuel sulfur level < 15 ppm	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>

*Check every 8 hours, change every 250 hours*

**DIFFERENTIAL FRONT WET BRAKES**  
Capacity: 44 liter

USE	CLIMATE
Preferred, extended	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid Synth XHP Ultra</b>		

*Change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 1000 hours*

**DIFFERENTIAL FRONT WET BRAKES + AXLE OIL COOLING**  
Capacity: 44 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>

*Change every 4000 hours*

# VOLVO WHEELED LOADERS L L150G

## STAGE IIIB/TIER 4I (2010-2014)



### DIFFERENTIAL REAR WET BRAKES

Capacity: 55 liter

USE	CLIMATE
Preferred, extended	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra***Change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT***Change every 1000 hours*

### DIFFERENTIAL REAR WET BRAKES + AXLE OIL COOLING

Capacity: 55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 3

**Agrifluid HT***Change every 4000 hours*

### TRANSMISSION AUTOMATIC Volvo HTL 221 4/4

Capacity: 44 liter

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol***Change every 2000 hours*

# VOLVO WHEELED LOADERS L L150G

## STAGE IIIB/TIER 4I (2010-2014)



### HYDRAULIC SYSTEM

Capacity: 150 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus H 68</b>	

*Change every 2000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Change every 2000 hours*

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

*Change every 4000 hours*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>

### COOLING SYSTEM

Capacity: 46 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Change every 48 months/ 6000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.